

Sec. 19-5.1 Table of dimensional standards

All primary structures shall be subject to the dimensional standards set forth in the following table. These standards may be further limited or modified by other applicable sections of this chapter. Rules of measurements and permitted exceptions are set forth in section 19-5.2, definitions/measurements.

Table 19-5.1-1: Table of Dimensional Standards							
District or Use	Lots			Setbacks Minimum (feet)			Height Maximum (feet) ⁸
	Max. Density and Min. Lot Area (sq. ft.)	Min. Width (feet)	Max. Coverage (percent) ¹¹	Front ¹	Side	Rear	
RESIDENTIAL DISTRICTS							
R-6	6,000	40	40	20	5	15	35
R-9	9,000	60					
RM-1	10 units/acre	40 for single-family detached; None for all other	40	20	5 for single-family detached and duplex; 15 for other uses	15 ¹⁶	40 ^{2, 12}
RM-1.5	15 units/acre						
RM-2 and RM-3	20 units/acre						
High-rise apartments in RM-3 and OD	1 acre	150	25 ³	25	25	25	None ⁴
Nonresidential uses in all residential districts	None	None	40	25	15	15 ¹⁶	40 ^{2, 12}
Accessory structures			50% of principal structure	NP	5	5	20 ⁹
NONRESIDENTIAL DISTRICTS							
OD	See ¹⁰ below	None	50	10	3 ⁵ or 10 ⁶	15 ¹⁶	40 ^{2, 12}
C-1	See ¹⁰ below	None	100	10	3 ⁵ or 10 ⁶	15 ¹⁶	40 ^{2, 12}
C-2	See ^{10, 14} below	None	100	10	3 ⁵ or 10 ⁶	15 ¹⁶	40 ^{2, 12}
C-3	See ^{10, 14} below	None	100	10	3 ⁵ or 10 ⁶	10 ¹⁶	40 ^{2, 12}
C-4	None	None	100	0	0	0	None ^{7, 12}
RDV	See ¹⁰ below	None	100	10 (20 Max)	3 ⁵ or 10 ⁶	3 ⁵ or 10 ^{6, 16}	40 ^{2, 12}
S-1	See ¹⁰ below	None	100	10	3 ⁵ or 10 ⁶	10 ¹⁶	40 ²
I-1	None	None	100	25	3 ⁵ or 25 ⁶	10 ¹⁶	40 ²
Accessory structures			10	NP	3 ⁵	3 ⁵	20 ⁹
NOTES: 1 See subsection 19-5.2.4(B), setback, front. 2 See subsection 19-5.2.9(C)(1), general. 3 See subsection 19-5.2.10, Lot coverage. 4 See subsection 19-5.2.9(C)(2), high-rise apartments. 5 Zero lot line or common wall construction is allowed. 6 If adjacent to a residential district. 7 Height may be limited by design guidelines for the central business district.							

8 See subsection 19-5.2.9, building height.

9 See subsection 19-4.4.2(E), maximum height.

10 No minimum lot area, maximum residential density is 20 units/acre.

11 Total impervious area shall not exceed 60 percent for lots with single-family detached homes and duplex dwellings, per section 19-6.9.

12 Single-family detached homes limited to 35 feet in height.

13 Development within the Unity Park Neighborhood District shall comply with the Table of Dimensional Standards in the Unity Park Neighborhood District Code.

14 Hotel or motel uses that are converted unit per unit to multi-family dwelling may exceed maximum density, per subsection 19-4.3.1(A)(5).

¹⁵ Minimum rear setbacks shall be increased to 25 feet for multifamily or nonresidential uses that abut property improved with single-family detached uses.

(Code 1997, § 19-5.1; Ord. No. 2007-52, § 19-5.1, 7-9-2007; Ord. No. 2008-25, 3-25-2008; Ord. No. 2009-22, 3-23-2009; Ord. No. 2012-49, 6-11-2012; Ord. No. 2014-68, 8-11-2014; Ord. No. 2015-05, ex.(19-5.1-1), 1-26-2015; Ord. No. 2016-17, ex. A, 3-28-2016; Ord. No. 2017-25, 2-27-2017; Ord. No. 2020-10, 1-27-2020; Ord. No. 2020-81, Ex. A, 11-9-2020)

Sec. 19-6.5.7 Nonresidential design standards

(O) Buffer zone adjacent to single-family uses.

- (1) Nonresidential development shall provide a buffer zone comprised of landscaping and screening elements, within the minimum setback from the lot line of any abutting property improved with a single-family detached use, as set forth in Sec. 19-6.2.3 Buffering and screening requirements.**

Sec. 19-6.8.9 Multifamily design standards

(B) Setbacks.

- (2) Multifamily residential buildings with three or more levels of stacked units shall be stepped back an additional ten feet ~~from the minimum required setback~~ for every floor above the second floor from property lines abutting a single-family detached dwellings use. Dormers and other minor roof features may project into the setback area.

- (a) Multi-family development shall provide a buffer zone comprised of landscaping and screening elements, within the minimum setback from the lot line of any abutting property improved with a single-family detached use, as set forth in Sec. 19-6.2.3 Buffering and screening requirements.**

Summary of Text Amendment:

Existing Text

New Text

ADDED PROPOSED REVISIONS:

- Interim process to appropriately address and adjudicate non-conforming situations/exception to design standards/undue hardships addressed under separate amendment.
- Clarified that the requirement pertains to commercial and multi-family uses that abut a property line of a single-family detached use.